

machinebidder

**ONLINE AUCTION SALE - 4 x MORI SEIKI SL-153SY (Ends: 15 May 2025)
Multi-Axis CNC Lathes with Sub-Spindle, LNS Barfeed, Gantry Loader &
Stacking System. Year 2000 & 2001. (170739)**

On instructions received from a UK PLC due to ongoing investment and removed for convenience of sale

4 x MORI SEIKI SL-153SY Multi-Axis CNC Lathes with Sub-Spindle, LNS Barfeed, Gantry Loader & Stacking System (Year 2000 & 2001)

Buyers Premium 18%

machinebidder

Lot no.	Description
1	 <p>MORI SEIKI SL-153SY 5 Axis CNC Lathe with Sub Spindle, Barfeed, Gantry Loader and Stacking Unit Fanuc MSG 501 Control. Year 2001</p> <p>Main spindle nose A2-5 fitted with HAINBUCH SRANNTOR Collet Chuck. Spindle power 7.5 kW. Spindle speeds to 5000 rpm. Max. bar diameter 56mm. Maximum turning dia. 300mm.C axis indexing precision 0.001 [°]. Sub spindle nose A2-5 fitted with FORKARDT 140mm dia. 3 Jaw Chuck. Spindle speeds to 5000 rpm. ...</p>
2	 <p>MORI SEIKI SL-153SY 5 Axis CNC Lathe with Sub Spindle, Barfeed, Gantry Loader and Stacking Unit Fanuc MSG 501 Control. Year 2001</p> <p>Main spindle nose A2-5 fitted with HAINBUCH SRANNTOR Collet Chuck. Spindle power 7.5 kW. Spindle speeds to 5000 rpm. Max. bar diameter 56mm. Maximum turning dia. 300mm.C axis indexing precision 0.001 [°]. Sub spindle nose A2-5 fitted with FORKARDT 140mm dia. 3 Jaw Chuck. Spindle speeds to 5000 rpm. ...</p>
3	 <p>MORI SEIKI SL-153SY 5 Axis CNC Lathe with Sub Spindle, Barfeed, Gantry Loader and Stacking Unit Fanuc MSG 501 Control. Year 2000</p> <p>Main spindle nose A2-5 fitted with HAINBUCH SRANNTOR Collet Chuck. Spindle power 7.5 kW. Spindle speeds to 5000 rpm. Max. bar diameter 56mm. Maximum turning dia. 300mm.C axis indexing precision 0.001 [°]. Sub spindle nose A2-5 fitted with FORKARDT 140mm dia. 3 Jaw Chuck. Spindle speeds to 5000 rpm. ...</p>
4	 <p>MORI SEIKI SL-153SY 5 Axis CNC Lathe with Sub Spindle, Barfeed, Gantry Loader and Stacking Unit Fanuc MSG 501 Control. Year 2000</p> <p>Main spindle nose A2-5 fitted with HAINBUCH SRANNTOR Collet Chuck. Spindle power 7.5 kW. Spindle speeds to 5000 rpm. Max. bar diameter 56mm. Maximum turning dia. 300mm.C axis indexing precision 0.001 [°]. Sub spindle nose A2-5 fitted with FORKARDT 140mm dia. 3 Jaw Chuck. Spindle speeds to 5000 rpm. ...</p>
