

SPECIFICATION

| | | | |
|----------------------------------|--|------------------|-----------------|
| MODE | A35x5000 | | |
| Swing over bed | 900mm | | |
| Swing over cross slide | 550mm | | |
| Swing over GAP | 1150mm | | |
| Center height | 440mm | | |
| Distance between enters | 5000 | | |
| Spindle bore, nose, speed | 153mm(6") | ASA-A2-11 | 7~700rpm |
| Spindle center | MT#6 | | |
| Main motor | 30HP | | |
| Thread cutting range | Inch:30~0.25TPI (70 SETS) Metric:1~120mm(62 sets) DP:1~120mm(80 sets) MP:30~0.25 TPI(53 sets) | | |
| Longitudinal feeds | 0.0032"~0.096"IPR (0.08~2.4mmMPR) | | |
| Cross feed | 0.0016"~0.048"IPR (0.04~1.2mmMPR) | | |
| Z axis rapid travel | 3000mm/min | | |
| X axis rapid travel | 1500mm/min | | |
| Z axis travel | 5000mm | | |
| X axis travel | 600m | | |
| Compound slide travel | 300mm | | |
| Tailstock quill diameter | 165mm rotating quill | | |
| Tailstock quill traverse | 200mm | | |
| Tailstock Center | MT#6 | | |
| Bed width | 610mm(24") | | |

***Design and specifications are subject to change without notice**